



PRODUCT SPECIFICATION

FITTINGS

A valmont COMPANY

RAIN PVC MANIFOLD FITTINGS

All Rain PVC fittings are designed to ensure easy assembly and quick maintenance of the starting manifolds of irrigation systems.

FEATURES


- Fitting Type: BSP Threaded
- Pressure Rating: 800 kPa
- Size: 1"
- Manufactured from: Polyvinyl chloride PVC
- O-ring: Special Elastomeric Nitrile Rubber (NBR)
- Minimum Operating Temperature: 4°C
- Maximum Operating Temperature: 50°
- Used in cold water irrigation systems only



NO TAPE



NO TOOLS



MODELS	CODE	INNER QTY	CTN QTY
Rain Manifold - 2 Port 1"	RNMAN21	1	50
Rain Manifold - 3 Port 1"	RNMAN31	1	30
Rain Manifold - 4 Port 1"	RNMAN41	1	30
Rain Adaptor 1" MxF	RNADMFF1	20	240
Rain Coupling 1" FxF	RNCOFF1	20	200
Rain Nipple 1"	RNNIP1	20	300
Rain Cross 1" FxFxF	RNCRSFFFF1	10	80
Rain Cross 1" MxFxF	RNCRSMFFF1	10	80
Rain Elbow 1" FxF	RNELBFF1	20	160
Rain Elbow 1" MxF	RNELBMFF1	20	200
Rain Tee 1" FxFM	RNTEEFFM1	20	120
Rain Cap 1"	RNCAP1	20	400

NOTE

HR Products recommends the installation and use of a master valve in the irrigation line prior to PVC Manifold fittings where the static pressure may be higher than the maximum pressure rating of the fittings.

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

FITTINGS_RAINMANIFOLD_V1.05.24

hrproducts.com.au



PERTH PH: 08 9484 6500 FAX: 08 9455 1680 hrsales@hrproducts.com.au	SYDNEY PH: 02 9616 1300 FAX: 02 9725 5283 infonsw@hrproducts.com.au	MELBOURNE PH: 03 8458 7400 FAX: 03 9457 7400 infovic@hrproducts.com.au	BRISBANE PH: 07 3080 6200 FAX: 07 3806 0533 infoqld@hrproducts.com.au	ADELAIDE PH: 08 8408 7200 FAX: 08 8341 0707 infoasa@hrproducts.com.au
--	---	--	---	---