

acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name WELD-ON 724 GRAY

Product category/ies GRAY CPVC SOLVENT CEMENT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses adhesive

CPVC solvent cement

1.3 Details of the supplier of the safety data sheet

Weld-On

17109 S. Main Gardena CA 90248-3127

United States

Telephone: 1-310-898-3300

e-mail: EHSInfo@ipscorp.com

Website: www.weldon.com

Importer: H R Products 207 Bannister Road

Canning Vale, Western Australia 6155

Tel. 1800998037

Emergency: - Call 13 11 26 (Poisons

Australia)

1.4 Emergency telephone number

Emergency information service 24 Hours - CHEMTEL: (800) 255-3924; International

(813) 248-0585

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Hazard class	Category
flammable liquid	2
acute toxicity (oral)	4
skin corrosion/irritation	2
serious eye damage/eye irritation	2
carcinogenicity	2
specific target organ toxicity - single exposure (respiratory tract irritation)	3

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

- Signal word danger

Australia: en Page: 1 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

- Pictograms

GHS02, GHS07, GHS08





- Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation. Causes serious eye irritation. H319 H335 May cause respiratory irritation. Suspected of causing cancer. H351

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P271 Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. P280 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction. P370+P378

Store in a well-ventilated place. Keep container tightly closed. P403+P233

Store in a well-ventilated place. Keep cool. P403+P235

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

tetrahydrofuran, cyclohexanone

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

SECTION 3: Composition/information on ingredients

Substances 3.1

Not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
tetrahydrofuran	CAS No 109-99-9	50 - < 75	Flam. Liq. 2 / H225 Acute Tox. 4 / H302 Eye Irrit. 2 / H319 Carc. 2 / H351 STOT SE 3 / H335
cyclohexanone	CAS No 108-94-1	10 - < 25	Flam. Liq. 3 / H226 Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335
methyl ethyl ketone	CAS No 78-93-3	1-<5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336

Australia: en Page: 2 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Name of substance	Identifier	Wt%	Classification acc. to GHS
Proprietary Additive	CAS No Proprietary	<1	Flam. Liq. 2 / H225 Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Carc. 2 / H351 STOT SE 3 / H335

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Australia: en Page: 3 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

Flash point -6.16 °F at 101.3 kPa

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Australia: en Page: 4 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
AU	cyclohexanone (anone)	108-94-1	WES	25	100					Н	WES
AU	tetrahydrofuran	109-99-9	WES	100	295					Н	WES
AU	titanium dioxide	13463-67-7	WES		10					i, noAsb_l ess1Sil	WES
AU	methyl ethyl ketone (MEK) (2- butanone)	78-93-3	WES	150	445	300	890				WES

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

i inhalable fraction

noAsb_less1S contains no asbestos and less than 1% free crystalline silica

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified)

Australia: en Page: 5 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
tetrahydrofuran	109-99-9	DNEL	72.4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
tetrahydrofuran	109-99-9	DNEL	96 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
tetrahydrofuran	109-99-9	DNEL	150 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
tetrahydrofuran	109-99-9	DNEL	300 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
tetrahydrofuran	109-99-9	DNEL	12.6 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects
cyclohexanone	108-94-1	DNEL	10 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
cyclohexanone	108-94-1	DNEL	20 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
cyclohexanone	108-94-1	DNEL	10 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
cyclohexanone	108-94-1	DNEL	20 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
cyclohexanone	108-94-1	DNEL	4 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic ef- fects
cyclohexanone	108-94-1	DNEL	4 mg/kg bw/ day	human, dermal	worker (industry)	acute - systemic ef- fects
methyl ethyl ketone	78-93-3	DNEL	600 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
methyl ethyl ketone	78-93-3	DNEL	1,161 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
tetrahydrofuran	109-99-9	PNEC	4.32 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
tetrahydrofuran	109-99-9	PNEC	0.432 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
tetrahydrofuran	109-99-9	PNEC	4.6 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
tetrahydrofuran	109-99-9	PNEC	23.3 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
tetrahydrofuran	109-99-9	PNEC	2.33 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
tetrahydrofuran	109-99-9	PNEC	2.13 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
cyclohexanone	108-94-1	PNEC	0.356 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)

Australia: en Page: 6 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Relevant PNECs of components of the mixture

	'					
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
cyclohexanone	108-94-1	PNEC	0.036 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
cyclohexanone	108-94-1	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
cyclohexanone	108-94-1	PNEC	2.69 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
cyclohexanone	108-94-1	PNEC	0.269 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)
cyclohexanone	108-94-1	PNEC	0.328 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	55.8 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	55.8 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	709 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	284.7 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	284.7 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)
methyl ethyl ketone	78-93-3	PNEC	22.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)
Proprietary Additive	Proprietary	PNEC	0.07 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)
Proprietary Additive	Proprietary	PNEC	0.007 ^{mg} / _l	aquatic organisms	marine water	short-term (single in- stance)
Proprietary Additive	Proprietary	PNEC	9 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in- stance)
Proprietary Additive	Proprietary	PNEC	0.062 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
Proprietary Additive	Proprietary	PNEC	0.016 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Australia: en Page: 7 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid (viscous)
Colour	gray
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	65 °C at 101.3 kPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	-21.2 °C at 101.3 kPa
Auto-ignition temperature	215 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	Decomposition onset temperature:
pH (value)	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Australia: en Page: 8 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Vapour pressure	17 kPa at 20 °C
Density and/or relative density	
Density	0.984 ^g / _{cm³} at 73 °F
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
Other safety parameters	
Flash point	-6.16 °F at 101.3 kPa
Other information	
Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	
- VOC content	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <= 400 g/L.

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidisers

Australia: en Page: 9 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Oral 679.4 ^{mg}/_{kq}

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
tetrahydrofuran	109-99-9	oral	500 ^{mg} / _{kg}
cyclohexanone	108-94-1	oral	500 ^{mg} / _{kg}
cyclohexanone	108-94-1	dermal	1,100 ^{mg} / _{kg}
cyclohexanone	108-94-1	inhalation: vapour	>6.2 ^{mg} / _I /4h
Proprietary Additive	Proprietary	oral	500 ^{mg} / _{kg}
Proprietary Additive	Proprietary	dermal	1,100 ^{mg} / _{kg}
Proprietary Additive	Proprietary	inhalation: vapour	>6.3 ^{mg} / _I /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Australia: en Page: 10 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Australia: en Page: 11 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 1133 IMDG-Code UN 1133 ICAO-TI UN 1133

14.2 UN proper shipping name

UN RTDG ADHESIVES
IMDG-Code ADHESIVES
ICAO-TI Adhesives

14.3 Transport hazard class(es)

UN RTDG 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number 1133
Class 3
Packing group II
Danger label(s) 3



Special provisions (SP) - (UN RTDG)

Excepted quantities (EQ) E2 (UN RTDG)

Limited quantities (LQ) 5 L (UN RTDG)

Emergency Action Code 3YE

Australia: en Page: 12 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 5 L
EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations (Australia)

Australian Inventory of Chemical Substances (AICS)

All ingredients are listed or exempt from listing.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed

Australia: en Page: 13 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Country	Inventory	Status
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
TR	CICR	not all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR

Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) CSCL-ENCS

DSL

ECSI

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory **IECSC**

INSQ ISHA-ENCS

KECI NZIoC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory **TSCA Toxic Substance Control Act**

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association

Australia: en Page: 14 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Australia: en Page: 15 / 16



acc. to Safe Work Australia - Code of Practice

WELD-ON 724 GRAY

Version number: 1.0 Date of compilation: 2022-11-29

Code	Text
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia: en Page: 16 / 16